

Print 6646-2.15E



Sketch of cross-section
(not actual size)

Applications

- Rotary Printing
- Flatbed Printing
- Sample Printing
- Coupon Printing
- Digital Printing

Properties/Advantages

- Low-noise HighTech-Fabric
- Minimized fluctuation of the Pitch Line – high printing precision
- Low belt weight – quick printing especially for long flatbed printers
- High resistance to solvents – even brief contact with acetone for cleaning is possible
- Simple and quick welding of the belt ends on the machine
- Reliable splice – no printout of the splice
- Repair possibility for minor belt damage

Basic technical data

Top face	0.8 mm hard urethane
Underside	impregnated fabric
Article no.	906646
d _{min} (mm)	60
Total thickness (mm)	2.15
k ₁ relaxed (N/mm width)	13
Weight (kg/m ²)	2.25
Permitted operating temperature	-30 to +70 °C (Printing)

Product Quick Info TR-906646-2 · 06/12
FMS · Reproduction of text or parts thereof only
with our approval.
Modifications reserved.

Forbo Siegling GmbH
Lilienthalstraße 6/8, D-30179 Hannover
Telefon +49 511 67 04 0, Fax +49 511 67 04 305
www.forbo-siegling.com, siegling@forbo.com